ALTUS 50 RTS RH 6/32


FEATURES & BENEFITS

- RTS Technology
- Suitable for interior & exterior application
- Standard multi-purpose motor
- Radio control allows blinds to be operated effortlessly and remotely
- 'My' Favourite setting sets blind to favourite position. Up, down and stop functions
- Compatible with Solar protection functions
- Round head motor
- Integrated antenna
- Memory capacity: 12 channels and 3 sensors
- Suitable for tubes diameter 50 mm (internal diameter)

SYSTEM COMPATIBILITY

• ROLLER SYSTEM

Note: Motor Options are also dependent on compatibility with our minimum motor widths chart.



TECHNICAL SPECIFICATIONS

POWER (NM):	6
NOMINAL VOLTAGE/FREQUENCY:	230V / 50 Hz
NOISE LEVEL:	52 dB(A)*
SPEED (RPM):	32
LIFT (KG):	16
MINIMUM MOTOR WIDTH:	700
RADIO FREQUENCY:	433.42 MHz
THERMAL TIME:	4mn
PROTECTION INDEX:	IP44
INSULATION CLASS:	Class I
CABLE TYPE:	Removal RRF or VVF

^{*}Sound pressure at a distance of 1mtr from the carrier product at nominal torque.

