

EXCLUSIVE TO **vertilux** **EUROVIEW™** Transparent



Why EUROVIEW™ Transparent?

The Vertilux Euroview™ fabric range is a high quality 100% Trevira CS fabric. Euroview™ is an open weave transparent fabric that is designed to assist with light glare reduction and insulation from harmful UV rays. An elegant sheer fabric, Euroview™ is available in a range of colours that coordinate well with other Vertilux fabric ranges and can be used with the Vertilux Roller Blind, Roman Blind or Panel Glide Systems.

Colour Range



Fabric Specifications

Quality:	100% Trevira CS (100% Free of PVC, Formaldehyde and Halogen to help reduce toxins in your environment)
Country of Origin:	Germany
Width:	Maximum Roller Width 3000mm Maximum Roman Width 2930mm
Weave & Opacity:	Twill weave to achieve transparent opacity.
Weight:	130 gr/m²
Thickness	0.38mm
Humid Room Suitability:	This fabric is suitable for use in humid rooms, such as bathrooms.
Custom Colour:	Available for orders of 500lm.
Printing:	Suitable for screen printing. Ask for more details.
Fire Classifications:	AWTA AS1530.2 1993 AWTA AS1530.3 1993 AWTA AS3837 1998 German Standard: DIN 4102 - B1 French Standard: M1
GBCA Recognised Third Party Product Certification Scheme	Yes – Global GreenTag ^{Cert™} GreenRate Level A
Oeko-Tex Certified:	Yes
Lightfastness:	Tested DIN EN ISO 105 B2: 6 - 7 Fabric with a 5+ result offers excellent resistance to the fading effect of light.
VOC test:	ASTM: D5116
Fabric Warranty:	7 years (internal use only)
Care Instructions:	Do not allow dust to accumulate. Gently vacuum with appropriate attachment. Do not dry clean. Test in an inconspicuous area with mild detergent solution before spot cleaning. When spot cleaning do not allow that area to become fully wet, use damp cloth only.

Light and Solar Optical Properties


Independently tested to DIN EN410: 1998

	Ts	Rs	As	Tv/Vlt	RI	AI	Tuv	O-F
WHITE	58	38	4	57	39	2	46	21
RICE	54	42	4	52	34	14	33	14
CLAY	45	37	18	40	21	39	28	14
DOVE	40	35	25	29	18	53	22	10
COAL	37	25	38	19	5	75	18	12
SPACE	39	23	38	21	4	75	25	17

Independently tested to ASHRAE 74-1988

Shading Coefficient			G-Value		
3mm Cl.	6mm Cl.	6mm H.A.	3mm Cl.	6mm Cl.	6mm H.A.
0.65	0.62	0.42	0.57	0.54	0.41
0.60	0.58	0.45	0.52	0.50	0.39
0.61	0.59	0.46	0.53	0.51	0.40
0.61	0.59	0.46	0.53	0.51	0.40
0.65	0.62	0.47	0.57	0.54	0.41
0.70	0.66	0.49	0.61	0.57	0.43

Legend to Light and Solar Optical Properties abbreviations: Ts: Solar Transmittance (%) As: Solar Absorbance (%) RI: Light Reflectance (%) Tuv: Ultraviolet Transmittance (%)
Rs: Solar Reflectance (%) Tv/Vlt: Visible Light Transmittance (%) AI: Light Absorbance (%) O-F: Openness Factor



BLINDS PROUDLY MADE IN AUSTRALIA
vertilux.com.au